



011 621 8300



EMAIL ORDERS:
sales@tagex.co.za



Tagex South Africa 412 Heidelberg Rd Tulisa Park Johannesburg +27 11 621 8300 www.tagex.co.za

INDUSTRIAL SUPPLIES

LITHIUM COMPLEX EP 2 WB-Red DATA SHEET

Characteristics:

LITHIUM COMPLEX EP2 is a multi-purpose lead free lithium complex grease, with excellent high temperature performance and long life capability. Good fretting corrosion performance, low water washout and good protection against bearing corrosion, combined with excellent mechanical stability and load-carrying capability makes it ideal multi-purpose grease.

LITHIUM COMPLEX EP2 consistently gives excellent high temperature performance and a wide operating temperature field from -20°C to $+150^{\circ}\text{C}$.

This product is suitable for all grease application. It is especially suitable for grease-lubricated rolling and sliding bearings at medium speed at normal and higher temperatures. Also recommended as Wheel Bearing Grease.

Data:

NLGI consistency	2
Colour	Red
Thickener Type	Lithium Complex
Drop point $^{\circ}\text{C}$	>240
Timken OK load kg.	> 27
Worked penetration	280
Base oil viscosity @ 40°C	200

Special features:

- ❖ Resistant to water wash out
- ❖ Protects bearings against corrosion
- ❖ Excellent lubrication properties
- ❖ Long life
- ❖ Economical
- ❖ Good anti-wear properties
- ❖ Excellent load carrying characteristics

Transport:

ADR/SDR Not dangerous goods.

Disposal:

EAK-Code: 12 01 12, As per country legislation.